

## VEHICLE HORN

[0001] This application is the U.S. National Stage of PCT/JP2005/000440, filed January 7, 2005, which claims priority from JP2004-004340, filed January 9, 2004, the entire disclosures of both applications being incorporated herein by reference thereto.

### BACKGROUND

~~{Technical Field}~~

[0002] The ~~present invention disclosure~~ relates to a vehicle horn that is mounted on a ~~vehicle~~ vehicle, such as a car, a ~~motoreycle~~ motorcycle, and ~~or~~ a special-purpose vehicle.

~~{Background Art}~~

[0003] Generally, as ~~this type of~~ such a vehicle horn, ~~known is a~~ vehicle horn with the following structure is known. Namely the vehicle horn has a recessed part projected outside which is formed on a bottom piece part of a cylindrical casing with a bottom, and an exciting coil which is formed by winding a winding wire around a coil bobbin and is housed in the recessed part. Provided in ~~In~~ a cylinder of the casing is ~~properly provided~~ a fixed iron core, a movable iron ~~core~~ core, which is displaced in an ~~axis~~ axial direction ~~in a state of when~~ being brought into contact with or separated from the fixed iron core based on excitation/non-excitation of the exciting coil, a fixed contact, and a movable contact intermittently switched based on the displacement of the movable iron coil in relation to the fixed contact or the like. ~~And further~~ Further, a terminal ~~member~~ member, provided with a pair of terminals for supplying electric power to the exciting ~~coil~~ coil, is arranged on an outer surface of the bottom piece part of the casing. In this type of vehicle horn, a warning sound is generated based on repeated intermittent switching between the movable contact and the fixed contact. ~~Meanwhile, an~~ An electrical noise is ~~also generated~~ generated, by arc ~~discharge~~ discharge, at the time of generating a warning sound. Such noise often has an ~~impact effect~~ on other electronic equipment. Thus, prevention of the noise has been proposed in recent years.

[0004] As an ~~improvement measure~~, improvement, it has been proposed to prevent the noise by connecting a noise preventing member in parallel to a wiring circuit of the fixed contact, the movable contact and the exciting ~~coil in parallel~~ coil. For example, a vehicle horn ~~constituted in such a manner that~~ having a ~~capacitor~~ capacitor, employed as the noise preventing ~~member is~~ member, fixed to an outer diameter part of the coil bobbin in the cylinder of the casing with a specific locking piece (Japanese Published Examined Utility Model Application No. ~~Sho-51-22612~~), Sho-51-22612). ~~a~~ Another vehicle horn has been

~~proposed miniaturizes in which the noise preventing member, in itself, is miniaturized by employing using a varistor as the noise preventing member, and the member. The varistor is provided in the vicinity of a fixed part where a plate for the fixed contact and a plate for the movable contact, in the cylinder of the casing, are fixed in an insulation-shape (Japanese Published Unexamined Patent Application No. Hei-5-48000), or the like, has been proposed. Hei-5-48000).~~

### SUMMARY

[0005] On the other hand, miniaturization of the vehicle horn has been strongly requested, and also miniaturization of the casing of the vehicle horn has been strongly demanded. However, both the vehicle horns disclosed in Japanese Published Examined Utility Model Application No. Sho-51-22612 and Japanese Published Unexamined Patent Application No. Hei-5-48000 are structured so as to provide the noise preventing member in the cylinder of the casing. Thus, it is necessary to consider the rise of the in temperature in the cylinder and to ensure a space for the noise preventing member, and the member. As a result, miniaturization of the casing ~~can be hardly~~ is difficult to realize. ~~realized.~~ In addition, an exclusive member for fixing the noise preventing member becomes necessary ~~for in~~ these vehicle horns, and not horns. Not only does the structure become ~~complicated~~ complicated, but also the cost increases. These problems are to be solved by the ~~present~~ invention.

#### [Disclosure of the Invention]

[0006] The ~~present~~ invention was made in order to ~~solve~~ solve, at least, the above problems. ~~The invention of claim 1 is a~~ A vehicle horn ~~constituted~~ is structured in such a manner that a recessed part projected ~~outside~~ outwardly is formed on a bottom piece part of a bottom of a cylindrical casing with a bottom, a casing. A coil bobbin of an exciting coil is housed in the recessed part and a terminal ~~member~~ member, provided with terminal plates for supplying electric power to a winding of the exciting ~~coil~~ coil, is arranged on an outer peripheral surface of the bottom piece part of the casing, ~~wherein and~~ a noise preventing member is provided in the terminal member.

[0007] Thus, the inner temperature of the casing has no ~~impact~~ effect on the noise preventing member and the casing can be miniaturized.

[0008] ~~In the invention of claim 2,~~ Further, the terminal member is provided with a pair of terminal plates, and the noise preventing member is provided between the pair of terminal plates. Thus, the inner temperature of the casing has no impact on the noise preventing member and the casing can be miniaturized.

[0009] ~~In the invention of claim 3,~~ In addition, the terminal member is made as a terminal unit in which the noise preventing member is built beforehand and the terminal unit is attached to an outer diameter side part of the recessed part of the bottom piece part of the ~~easing in the invention of claim 1 or 2.~~ casing. Thus, ~~assembling assembly~~ work can be simplified.

[0010] ~~In the invention of claim 4, the~~ The terminal member is provided so ~~as not to be projected project~~ further outside than the recessed part of the bottom piece part of the ~~easing in the invention of claim 1, 2 or 3.~~ casing. Thus, when the horn is installed, a space between it and other members can be reduced.

[0011] ~~In the invention of claim 5, the~~ The noise preventing member is provided in a space formed in the terminal member and the space is filled with a resin ~~material in the invention of claim 1, 2, 3 or 4.~~ material. Thus, the noise preventing member can be protected and reliably fixed.

[0012] ~~According to the invention of claim 1, since~~ Because the inner temperature of the casing has no impact on the noise preventing member, the noise preventing member can be protected. In addition, the casing can be miniaturized.

~~———[0013]—— According to the invention of claim 2, because the inner temperature of the casing has no impact on the noise preventing member, the noise preventing member can be protected. In addition, the casing can be miniaturized.~~

~~———[0014]—— According to the invention of claim 3, the assembling work can be simplified.~~

~~———[0015]—— According to the invention of claim 4, when the horn is installed, the space between it and other members can be reduced.~~

~~———[0016]—— According to the invention of claim 5, the noise preventing member can be protected and reliably fixed.~~

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The disclosure will be made with respect to the drawings in which:

[0014] Fig. 1 is a partial side cross sectional view of a horn;

[0015] Fig. 2 is a front view of a state where members are attached to a casing;

[0016] Fig. 3 is a rear view of the horn;

[0017] Fig. 4(A) is a front view of a terminal unit, and Fig. 4(B) is a rear view of the terminal unit; and

[0018] Fig. 5(A) is a cross sectional view taken along line ~~X-X~~ 5A-5A in Fig. 4(A), Fig. 5(B) is a plan view of Fig. 4(A), and Fig. 5(C) is a cross sectional view taken along line ~~X-X~~ 5C-5C in Fig. 4(B).

### DETAILED DESCRIPTION OF EMBODIMENTS

~~[Best Mode for Carrying Out the Invention]~~

[0019] Next, an exemplary embodiment ~~of the present invention~~ will be described hereinafter with reference to Figs. 1 to 5.

[0020] In the figures, the reference numeral 1 denotes a vehicle ~~horn, and a~~ horn. A casing 2 ~~constituting for~~ the horn 1 is formed cylindrically with a bottom. A recessed part 2b projecting ~~outside outwardly~~ is formed on the center part of a bottom piece part 2a of the casing 2 (bottom as used in the context of the casing is toward the right in Fig. 1). A fixed iron core 3 penetrates an axially center part of the recessed part ~~2-2b~~ and is supported position-adjustably in an axial direction by a fixing nut 3a.

[0021] The reference numeral 4 denotes a coil bobbin. The coil bobbin 4 is composed of a cylinder 4a and flanges 4b, which are extended to outer diameter sides ~~of from~~ both ends of the cylinder ~~4a-4a, respectively respectively,~~ and are integrally formed with the cylinder 4a. An exciting coil C is constituted in such a manner that a winding 5 is wound around the periphery of the cylinder 4a. The coil bobbin 4 is housed in the recessed part ~~2b with the 2b.~~ The fixed iron core 3 is inserted into the cylinder 4a and one of the flanges 4b is supported by the bottom piece part 2a of the casing 2. Further, an attachment piece part 4c (Fig. 2) and a terminal fixing piece part 4d, which are faced to each other in radial direction and ~~projected project~~ toward an outer diameter, are integrally formed on a peripheral edge of the flange 4b of the coil bobbin 4 at the opening side of the casing 2. The attachment piece part 4c is fixed to an outer diameter side bottom piece part 2c formed at an outer diameter side of the recessed part 2b of the casing 2 via a pin 2d.

[0022] The terminal fixing part 4d is arranged at a facing part of a pair of through holes 2e, 2f opened in a circumference direction of the casing outer diameter side bottom piece part 2c. A pair of through holes 4e, 4f are opened which penetrate the casing through holes 2e, 2f respectively. An end 5a of the winding ~~5-5,~~ constituting the exciting coil C-C, is pulled out and wired from the coil bobbin cylinder 4a in the vicinity of the through hole 4e ~~among of~~ the pair of through holes 4e, 4f. As described below, a first terminal pin ~~6-6,~~ made of a conductive ~~member member,~~ is provided so as to penetrate coil bobbin through hole 4e



and the casing through hole 2e. Therefore the winding end 5a is electrically connected to the first terminal pin 6.

[0023] Additionally, the other end 5b of the winding 5 of the exciting coil C is pulled out and wired from the cylinder 4a in the vicinity of the coil bobbin through hole 4f. Further, a base end 7b of a fixing plate 7, which is constituted by the conductive plate member and in which a through hole 7a is opened, and a base end 8b of a movable plate 8, which is constituted by the conductive plate member and in which a through hole 8a is opened, are provided ~~aside of~~ in alignment with the through hole 4f. A second terminal pin 9 made of a conductive member, is provided so as to penetrate the coil bobbin 4 through hole 4f which is partly defined by a lip, the fixing plate through hole 7a, the movable plate through hole 8a and the casing through hole 2f, respectively. Therefore, the fixing plate 7 is electrically connected to the second terminal pin 9 and the movable plate 8 is insulated from the second terminal pin 9 by the lip of the coil bobbin 4 which lies between the movable plate 8 and the second terminal pin 9, ~~and the~~ The movable plate 8 is electrically connected to the other winding end 5b. In addition, an insulating material 10 is interposed between the fixing plate 7 and the movable plate 8, and therefore the fixing plate 7 is insulated from the movable plate 8. Moreover, a top end 7c (top and bottom used in the context of the plates 7, 8 refer to the portrayal in Fig. 1) of the fixing plate 7 is fixed by a fixing piece 4g extended from the flange 4b of the coil bobbin 4 at the opening side of the casing 2.

[0024] A fixed contact 7d is formed on the fixing plate 7 so as to ~~be projected~~ project toward the movable plate 8 side, a movable contact ~~8e-8c~~, facing the fixed contact ~~7d~~ 7d, is formed on the movable plate 8 so as to ~~be projected~~ project toward the fixing plate 7 side. The movable contact 8c is brought into contact with and electrically connected to the fixed contact 7d in the natural state. Thus, when electric power is supplied via the first and second terminal pins 6, 9 in the contact state, electric power is supplied to the exciting coil C.

[0025] A peripheral edge of a diaphragm 11 is integrally fixed to an opening edge of the casing 2, and a long shaft-shaped movable iron core 12 is integrally provided at the center of the diaphragm 11. An end surface 12a of the movable iron core 12 is arranged so as to adjacently face an end surface (inside top end surface) 3b of the fixed iron core 3 inside the casing 2 with a predetermined gap G. Further, as described above, the exciting coil C is supplied with the electric power to magnetize the fixed iron core 3 so that the movable iron core 12 is attracted to the fixed iron core 3 based on the flexibility of the diaphragm 11 and displaced.

[0026] A step 12b is formed on a peripheral surface of the movable iron core 12. The step 12b forcibly displaces the movable plate 8 in a ~~direction~~, direction where it moves away from the fixed plate 7, based on the displacement of the movable iron core 12 toward the fixed iron core 3 side, and ~~makes~~ causes the movable contact 8c move away from the fixed contact 7d. In this state, the exciting coil C is not energized and degaussed.

[0027] ~~The reference~~ Reference numeral 13 denotes a terminal unit (corresponding to the terminal member of the ~~present invention~~ in this disclosure) in which penetrating top ends of the first and second terminal pins 6, 9, projecting toward ~~projected to~~ the outer surface of the casing outer diameter side bottom piece part ~~2e-2c~~, are housed. A case body 14 (Figs. 3-5(c)), constituting the terminal unit ~~13-13~~, includes a bottom piece 14a along the casing outer diameter side bottom piece part ~~2e-2c~~. and The case body 14 is formed in a box-shape, and a space S is formed between side pieces 14b, 14c provided at both ends-sides of the case body 14 in the ~~circumference~~ circumferential ~~direction respectively of the casing 2.~~ Base ends 15a, 16a of the first and second terminal plates (corresponding to a pair of terminal plates of the present invention) 15, 16 are ~~buried in~~ positioned within the side pieces 14b, 14c respectively. A pair of through holes 14d, 14e respectively formed in the side pieces 14b, 14c are provided so as to respectively communicate with through holes 15b, 16b respectively formed in the base ends 15a, 16a. The penetrating top ends of the first and second terminal pins 6, 9 penetrating from the inside of the casing 2 ~~are made to penetrate~~ the through holes 14e, 14f and the through holes 15b, 16b respectively. Thus, the first and second terminal pins 6, 9 are electrically connected to the first and second terminal plates 15, 16 respectively.

[0028] A capacitor ~~17-17~~, which is a noise preventing ~~member-member~~, is housed in the space S formed between the side pieces 14b, 14c of the case body 14. A pair of connecting lines 17a, 17b extended from the capacitor 17 are electrically connected to the first and second terminal plates 15, 16 exposed outside via notches 14f, 14g respectively formed ~~on-in~~ the side pieces 14b, 14c so as to communicate with the space S, respectively, by means of such as soldering. Thus, the noise preventing member 17 is arranged in such wiring state as to be connected to a contact part of the fixed contact 7d and the movable contact 8c in parallel.

[0029] The space S, in which the noise preventing member 17 is provided, is then filled with an insulating resin material 18, and thus the noise preventing member 17 is ~~buried~~ encased by the resin material 18.

[0030] With the structure ~~mentioned above~~ described above, the terminal unit 13 is attached to the casing 2 in the following manner. Namely, the bottom piece 14a is brought into contact with the casing outer diameter side bottom piece part 2c, the resin material 18 filling side is exposed to the outside (or right side in Fig. 1), the first and second terminal pins ~~6-6, and 9 projected~~ projecting outside outwardly (to the right side of Fig. 1) from the casing outer diameter side bottom piece part 2c are inserted into the casing through holes 14d, 14e and the first and second terminal plate through holes 15b, 16b respectively, and the penetrating ~~top~~ ends of the first and second terminal pins 6, 9 are caulked. By this attachment, the casing 2, the coil bobbin 4, the fixing plate 7, the movable plate 8, the one winding end 5a and the other winding end 5b are electrically connected to each other as described above and integrally ~~fixed, the fixed~~. The first and second terminal pins 6, 9 are electrically connected to the first and second terminal plates ~~15 and 16~~ 15, 16 respectively, and the terminal unit 13 is integrally fixed to the casing 2 by one caulking operation.

[0031] Here, a side piece (inner ~~diameter radial~~ side piece) 14h ~~of at an inner diameter radial side~~ of the case body 14 is formed in an arc-shape so as to adjacently face the peripheral surface of the casing recessed part ~~2b, and the 2b~~. The thickness T of the case body 14 in an axial direction (the thickness in a box depth direction) is set so as to be smaller than the projecting amount of the casing recessed part ~~2b toward the outside. 2b~~. The terminal unit 13 is set so as to not to be projected project further outside than the bottom piece part 2a when attached to the casing.

[0032] Moreover, ~~top~~ ends of the first and second terminal plates 15, 16 ~~are projected project~~ toward the outer ~~diameter radial~~ side from a side piece 14i ~~in an at the outer diameter radial side of casing body 14, and an 14~~. An outer coupler (not shown) is fitted with the projecting part. ~~The electric~~ Electric power is supplied to the first and second terminal pins 6, 9 via the first and second terminal plates 15, 16 from the outside and ~~sent is sent~~ to the exciting coil C.

[0033] In the horn 1 thus structured, when the switching operation (not shown) is performed, the electric power is supplied to the first and second terminal pins 6, 9, the exciting coil C is energized and excited via the fixed contact 7d and the movable contact 8c being brought into contact with each other, and the movable iron core 12 is displaced toward the fixed iron core 3 side. Thus, the movable contact 8c moves away from the fixed contact 7d, and the exciting coil C no longer is ~~not~~ energized. Then the movable iron coil 12 moves away from the fixed iron core 3, and ~~thus~~ the movable contact 8c again comes into contact

with the fixed contact 7d ~~again~~ and the exciting coil C is excited. A warning sound is generated by repeating this operation.

[0034] As described above, in the embodiment structured as the above, when the electric power is supplied to the first and second terminal pins 6, 9 via the first and second terminal plates 15, 16 based on the switching operation (not shown), an intermittent switching between the fixed contact 7d and the movable contact 8c is repeated and the warning sound is generated. In this case, because the noise preventing member 17 is connected to the fixed contact 7d and movable contact 8c in parallel, the noise due to ~~repeating of the~~ the repeated intermittent switching between the fixed contact 7d and the movable contact 8c is prevented and ~~the a~~ horn 1 having ~~an~~ excellent performance can be obtained.

[0035] In this case, the noise preventing member 17 is not provided in the cylinder of the casing 2, but is housed in the terminal unit 13 which is provided outside of the casing 2 in order to supply the electric power. Thus, the noise preventing member 17 is not affected by ~~an the atmosphere~~ atmospheric temperature in the casing 2 and ~~can be~~ is protected based on its own ~~the~~ heat resistance ~~guarantee to~~ temperature. Further, it is unnecessary to ensure an exclusive space in the cylinder of the casing 2 for the noise preventing member 17, ~~and so~~ that the casing can be miniaturized. Furthermore, it is unnecessary to provide an exclusive member for attachment of the noise preventing member, the structure inside the cylinder of the casing 2 can be simplified, and cost can be reduced.

[0036] Additionally, because the noise preventing member 17 is provided in the space S between the terminal plates 15, 16 which are arranged in the ~~circumference~~ circumferential direction with the predetermined gap beforehand, it is unnecessary to provide ~~the additional~~ space for the noise preventing member 17.

[0037] Additionally, because the noise preventing member 17 can be built in the terminal unit 13 together with the first and second terminal plates 15, 16, in the state where the first and second terminal plates 15, 16 are already wired, enabling the terminal unit 13 to be attached to the casing 2, the wiring of the noise preventing member 17 and assembling work are simplified, and the horn 1 can be effectively manufactured.

[0038] Additionally, because the thickness of the terminal unit 13 in the axial direction is set so as to ~~to be~~ larger than the projecting amount of the recessed part 2b of the casing 2, there is no problem such that the space for provision of the horn 1 is enlarged by the terminal unit 13, ~~and a~~ 13. As a result, the space between the horn 1 and members provided in the vicinity can be reduced ~~in provision of~~ when the horn 1 is provided.



[0039] Further, the noise preventing member 17 is provided in the space S formed between ~~burying-encased~~ parts, which face each other, of the first and second terminal plates 15, 16 of the terminal unit 13. The space S is filled with the resin material 18 so that the noise preventing member 17 is ~~buried-encased~~ in and integrally fixed to the terminal unit 13. Thus, the noise preventing member 17 can be protected, a ~~trouble-problem~~ such ~~that-as~~ the noise preventing member 17 ~~falls-falling off by-as a result of~~ vibration is avoided, and the noise preventing member 17 can be reliably fixed.

[0040] Additionally, when forming a product in which the noise preventing member 17 is to be provided and a product in which the member 17 is not to be provided, it is only required to prepare the terminal unit 13 in which the noise preventing member 17 is ~~built~~ included and the terminal 13 in which the member 17 is not ~~built~~included. That is, the specification of the casing 2 side does not vary for each product. Thus, components can be ~~made-made in~~ common and low-cost can be ~~realized, in-realized~~. In addition, quality management can be simplified. Further, when the terminal unit 13 in which the noise preventing member 17 is ~~to-be-built~~ included and the terminal 13 in which the member 17 is not ~~to-be-built~~ included are formed, it is only required to form two types of terminal units of which the shapes of the parts exposed outside are different from each other. Thus, ~~work-it is unnecessary-not necessary to attach identifying such as attaching-marks different from each other-to identify whether the horn-horn is provided with the noise preventing member and-or the horn is not provided with no-the noise preventing member respectively beforehand, and distinguishing them-becomes-the two different terminal units is~~ easy.

[0041] Moreover, the ~~present-invention~~disclosure, as a matter of course, is not limited to the above described exemplary embodiment. One sheet of a terminal plate is provided in the terminal member in the case of a horn in which a body ground is performed. However, even in this case, a space can be provided adjacently to the terminal plate, the noise preventing member can be built in the space, and the space can be filled with the resin material. Thus, ~~similarly-similar~~ to the above described exemplary embodiment, the noise preventing member can be protected against the ~~atmosphere-atmospheric~~ temperature, etc., and can be reliably fixed or positioned.

~~{Industrial Applicability}~~

[0042] As described above, a vehicle horn according to the ~~present-invention~~ disclosure serves as a horn that is mounted on a general-purpose type vehicle such as a car

and a motorcycle, a special-purpose vehicle or the like, and is, in particular, ~~is~~-suitable for the general-purpose type vehicle.

## ABSTRACT OF THE DISCLOSURE

~~In a vehicle horn with a~~ A noise preventing member of a vehicle horn ~~the object of the invention is to protect~~ is protected the noise preventing member and to realize leads to a miniaturization of the horn. A recessed casing part 2b ~~projected outside projecting outwardly~~ is formed ~~on~~ as a bottom piece part 2a ~~portion of a cylindrical easing 2 with a bottom, casing.~~ a ~~A~~ coil bobbin 4 of an exciting coil C is housed in the recessed casing part 2b, and a terminal unit ~~13~~ unit, provided with a pair of terminal plates 15 ~~and 16~~ for supplying electric power to a winding 5 of the exciting ~~coil C~~ coil, is attached to ~~a~~ the casing outer peripheral surface of ~~an outer diameter side bottom piece part 2c of a portion of the easing 2, casing.~~ a ~~A~~ noise preventing member 17 is provided in a space between the terminal plates 15 ~~and 16~~ of the terminal unit ~~13~~, ~~and~~ unit. ~~the~~ The space is filled with a resin material 18 so that the noise preventing member 17 is ~~buried~~ encased in the resin ~~material 18.~~ material.